Printing date 01/15/2024 Revised On 01/15/2024

1 Identification of the substance and manufacturer

Trade name: PINK FLUORESCENT

Product code: 0000200379

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**







Signal word

Danger

Extremely flammable aerosol. **Hazard statements**

Contains gas under pressure; may explode if heated.

May damage fertility or the unborn child. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description:

Dangerous components:		
	VM&P Naphtha	10-15%
	propane	10-15%
	Calcium Carbonate	10-15%
106-97-8	n-butane	5-10%
	xylene (mix)	≥5-<10%
	Mineral Spirits	1-5%
108-88-3	Toluene	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 01/15/2024 Revised On 01/15/2024

Trade name: PINK FLUORESCENT

Special hazards:

Protective equipment for

firefighters:

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up: Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) | Short-term value: 1000 ppm

(EX)

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm REL (USA) Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm

BEI, A4

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Long-term value: 20 ppm BEI, OTO, A4 TLV (USA)

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 01/15/2024 Revised On 01/15/2024

Trade name: PINK FLUORESCENT

Avoid contact with the skin.

Avoid contact with the eves and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Aerosol. Odor: **Aromatic** Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. -44 °C (-47.2 °F) **Boiling point:**

Flash point: -19 °C (-2.2 °F) Extremely flammable. Flammability (solid, gas): **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % **Upper Explosion Limit:** Vapor pressure: Not determined.

Between 0.77 and 0.85 (Water equals 1.00) Relative Density:

Vapor density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined.

Water: 31.7 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Not fully evaluated.

Chemical stability:

No dangerous reactions known. Possibility of hazardous reactions:

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

1330-20-7 xylene (mix)

Oral LD50 8,700 mg/kg (rat) LD50 2,000 mg/kg (rbt) Dermal Inhalative LC50/4 h 6,350 mg/l (rat)

Information on toxicological effects: No data available.

Irritant to skin and mucous membranes. Skin effects:

Eye effects: No irritating effect. Sensitization: No sensitizing effects known.

12 Ecological information

Hazardous for water, do not empty into drains.

Aquatic toxicity: Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. No further relevant information available. Other adverse effects:

1

Safety Data Sheet

Printing date 01/15/2024 Revised On 01/15/2024

Trade name: PINK FLUORESCENT

(Contd. of page 3)

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation: Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 Gases

Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ŭ

Packaging Group: UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix) 108-88-3 Toluene

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

1330-20-7 xylene (mix)

16 Other information

Contact: Regulatory Affairs