Safety Data Sheet

Printing date 01/24/2024 Revised On 01/24/2024

1 Identification of the substance and manufacturer

Trade name: **GOOD GRIP YELLOW**

Product code: 0000160089

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated. Gases under Pressure - Liquefied gas

H315 Causes skin irritation. Skin Irritation 2

Eye Irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms







GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation. Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

25-50%
10-15%
≥5-<10%
5-10%
5-10%
1-5%
1-5%
1-5%
>

Safety Data Sheet

Printing date 01/24/2024 Revised On 01/24/2024

Trade name: GOOD GRIP YELLOW

(Contd. of page 1)

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

Protective equipment for

firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for

Use respiratory protective device against the effects of fumes/dust/aerosol.

containment and cleaning up: Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection		
Components with limit values that require monitoring at the workplace:		
67-64-1 Acetone		
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 590 mg/m³, 250 ppm	
TLV (USA)	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI	
74-98-6 propane		
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)	
108-88-3 Toluene		

TLV (USA)	see Appendix F Minimal oxygen content (
108-88-3 Toluene			
PFL (USA)	Long-term value: 200 ppm		

*10-min peak per 8-hr shift

Ceiling limit value: 300; 500* ppm

Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm REL (USA)

Long-term value: 20 ppm TLV (USA) BEI, OTO, A4

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm

(EX)

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/24/2024 Revised On 01/24/2024

Trade name: GOOD GRIP YELLOW

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene
0.3 mg/g creatinine
Medium: urine

Time: end of shift Parameter: o-Cresol with hydrolysis (background)

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment:A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. Boiling point: -44 °C (-47.2 °F) -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % Vapor pressure: 1.7 Vol % Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

0.0 %

Vapor density Not determined.
Evaporation rate Not applicable.
Partition coefficient: n-octonal/water: Not determined.
Solubility: Not determined.
Viscosity: Not determined.

10 Stability and reactivity

Water:

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

(Contd. on page 4)

1

Printing date 01/24/2024 Revised On 01/24/2024

Trade name: GOOD GRIP YELLOW

13463-67-7 titanium dioxide

(Contd. of page 3)

>20,000 mg/kg (rat) Oral LD50 Dermal LD50 >10,000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

No further relevant information available. Bioaccumulative potential: No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation: Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT UN1950

Aerosols, flammable DOT **ADR** 1950 AEROSOLS

Transport hazard class(es):

2.1 Gases Class Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ŭ

Packaging Group:

UN "Model Regulation": **UN 1950 AEROSOLS, 2.1**

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. Comission (CPSC):

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

16 Other information

67-64-1 Acetone

Contact: Regulatory Affairs