Revised On 01/15/2024

1 Identification Trade name: WHITE 0000162002 Product code: Paint and coatings application. **Recommended use:** Uses advised against: Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA Manufacturer/Supplier: Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 phone: 815-895-9101 www.seymourpaint.com www.seymourpaint.com 1-800-255-3924 **Emergency telephone number:** 2 Hazard(s) identification Classification of the substance or mixture Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Skin Irritation 2 H315 Causes skin irritation. Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation. Toxic to Reproduction 1B H360 May damage fertility or the unborn child. Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. Additional information: **GHS Hazard pictograms** GHS02 GHS04 GHS07 GHS08 Signal word Danger Hazard-determining components of Toluene labeling: titanium dioxide Extremely flammable aerosol. Hazard statements Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of causing cancer. Route of exposure: Inhalation. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations. **Physical dangers:** Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical D	escription:	This product is a mixture of the substances listed below with nonhazardous additions.		
	Dangerous components:			
74-98-6	propane		15-25%	
	n-butane		10-15%	
1317-65-3	Calcium Carbonate		10-15%	
108-88-3			10-15%	
	VM&P Naphtha		5-10%	
	titanium dioxide		1-5%	
64742-47-8	Mineral Spirits		1-5%	

4 First-aid measures

Description of first aid measures	
After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	Rinse out mouth and then drink plenty of water.
3	

(Contd. on page 2)

Revised On 01/15/2024

Safety Data Sheet acc. to OSHA HCS

Printing date 01/15/2024

Printing date 01/15/2024	Revised On 01/15/2024
Trade name: WHITE	
	(Contd. of page 1) (Contd. of page 1)
Information for doctor:	
Most important symptoms and effects:	Dizziness
Indication of any immediate medica	d la
attention needed:	No further relevant information available.
5 Fire-fighting measures	
Extinguishing media	
Extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Protective equipment for	Can form explosive gas-air mixtures.
firefighters:	A respiratory protective device may be necessary.
Additional information	Cool endangered receptacles with water spray.
6 Accidental release measures	
Personal precautions, protective	
equipment and emergency procedures:	Wear protective equipment. Keep unprotected persons away.
	Use respiratory protective device against the effects of fumes/dust/aerosol.
Environmental precautions: Methods and material for	Do not allow product to reach sewage systems or ground water.
containment and cleaning up:	Ensure adequate ventilation.
7 Handling and storage	
Precautions for safe handling Fire/explosion protection:	Use only in well ventilated areas. Keep respiratory protective device available.
	Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from
	electrostatic discharges.
Conditions for safe storage: Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
	Store lockéd up.
8 Exposure controls/personal pro Components with limit values that	
require monitoring at the	
workplace:	The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
	At this time, the other constituents have no known exposure limits.
74-98-6 propane	
PEL Long-term value: 1800 mg/m ³ , 1	
REL Long-term value: 1800 mg/m ³ , 1 TLV see Appendix F Minimal oxygen	
106-97-8 n-butane	
REL Long-term value: 1900 mg/m ³ , 8	00 ppm
TLV Short-term value: 1000 ppm	
(EX) 108-88-3 Toluene	
PEL Long-term value: 200 ppm	
Ceiling limit value: 300; 500* ppr	n
*10-min peak per 8-hr shift REL Short-term value: 560 mg/m³, 15	50 ppm
Long-term value: 375 mg/m³, 10	
TLV Long-term value: 20 ppm	
BEI, OTO, A4	(Contd. on page 3)
	(

Printing date 01/15/2024

Trade name: WHITE

Revised On 01/15/2024

Trade name: WHITE	
	(Contd. of page 2)
Ingredients with biological limit va	alues:
108-88-3 Toluene	
BEI 0.02 mg/L Medium: blood Time: prior to last shift of workv Parameter: Toluene	veek
0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene	
0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydro	lysis (background)
Exposure controls Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Store protective clothing separately.
Breathing equipment:	Store protective clothing separately. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical
Hand protection:	hygiene. Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles
9 Physical and chemical properti	ies
General Information: Appearance: Odor: Odor threshold:	Aerosol. Aromatic Not determined.
pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. -44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Decomposition temperature:	Not determined.

Auto igniting: Product is not self-igniting. Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 Danger of explosion: degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Lower Explosion Limit: Upper Explosion Limit: Vapor pressure: Vapor Pressure: Relative Density: 40 PSI 2750 hPa 40 PSI, 2750 hPa Between 0.77 and 0.85 (Water equals 1.00) Vapor density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined. Dynamic: Kinematic: Not determined. Not determined. Water: 28.8 %

10 Stability and reactivity		
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. temperatures.	Do not warehouse in subfreezing
Possibility of hazardous reactions: Conditions to avoid Incompatible materials: Hazardous decomposition:	No dangerous reactions known. No further relevant information available. No further relevant information available. No dangerous decomposition products known.	

Printing date 01/15/2024

Revised On 01/15/2024

	(Contd. of page 3)
11 Toxicological information	
LD/LC50 values that are relevant for	or classification:
13463-67-7 titanium dioxide	
Oral LD50 >20,000 mg/kg	(rat)
Dermal LD50 >10,000 mg/kg	
Inhalative LC50/4 h >6.82 mg/l (rat)	
Skin effects:	No irritant effect.
Eye effects: Sensitization:	No irritating effect. No sensitizing effects known.
IARC (International Agency for Res	
13463-67-7 titanium dioxide	2B
NTP (National Toxicology Program	
None of the ingredients is listed.	·
12 Ecological information	
Toxicity Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons
	(HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Results of PBT and vPvB assessm PBT:	ent Not applicable.
vPvB:	Not applicable.
Other adverse effects:	No further relevant information available.
Waste treatment methods Recommendation: Recommended cleansing agent:	or cut empty containers with electric or gas torches. Completely empty cans should be recycled. Water, if necessary with cleansing agents.
14 Transport information	
UN-Number	UN1950
DOT	UN1950
	UN1950
UN proper shipping name: DOT	AEROSOLS, flammable
Transport hazard class(es):	
Class Marine nellutenti	2.1 Gases
Marine pollutant: Special precautions for user:	No Warning: Gases
EMS Number:	F-D,S-Ŭ
DOT Declaring Organization	
Packaging Group:	
15 Regulatory information	
Reglamentación y legislación en m	nateria de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla
Toxic Substances Control Act	
(TSCA): Consumer Product Safety	All hazardous ingredients are found on the inventory list of substances.
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
Hazardous Air Pollutants	
108-88-3 Toluene	
California Proposition 65 chemical	s known to cause cancer:
13463-67-7 titanium dioxide	
	birth defects or reproductive harm:
CANADIAN ENVIRONMENTAL PROTECTION ACT:	All hazardous ingredients for this product appear on the Canadian Domestic Substance List.
	(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/15/2024

Trade name: WHITE

	(Contd. of page 4)
EPA:	
None of the ingredients is listed.	
GHS label elements Precautionary statements Chemical safety assessment:	The product is classified and labeled according to the Globally Harmonized System (GHS). Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations. A Chemical Safety Assessment has not been carried out.
features and shall not establish a lega	d on our present knowledge. However, this shall not constitute a guarantee for any specific product lly valid contractual relationship.
Contact: Date of preparation / last revision	Regulatory Affairs 01/15/2024
Abbreviations and acronyms:	IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent EPA: Environmental Protection Agency IARC: International Agency for the Research of Cancer NIOSH: National Institute for Occupational Safety and Health TSCA: Toxic Substances Control Act CPSC: Consumer Product Safety Commission TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit EB: Biological Exposure Limit Flammable Aerosols 1: Aerosols - Category 1 Gases under Pressure - Liquefied gas: Gases under pressure – Liquefied gas Skin Irritation 2: Skin corrosion/irritation – Category 2 Toxic to Reproduction 1B: Reproductive toxicity – Category 1B Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2