

TECHNICAL DATA SHEET



SPRUCE METALLICS AND LACQUERS

A fast drying lacquer spray paint that provides durable indoor and outdoor protection. Resistant to the effects of weather and many chemicals. Resists abrasion and heat (250F). Bare surfaces or rusted metal surfaces should first be primed with our Spruce primers to ensure proper adhesion.

Suggested Uses:

Metal, wood and wicker Furniture Toys Boats Bikes

Packaging:

Cans per case Shipping weight per case Container Label weight Shipping Classification Hazard Class 12 15 lbs. 16 fluid ounce can 12 ounces (340 grams) limited quantity, UN 1950 2.1

Properties:		Dry Time*:		
Coverage Cleanup Flammability Specific Gravity	Up to 15 square feet Paint or lacquer thinner Extremely Flammable 0.86	To touch To recoat	5 minutes 20 minutes	
Solids Content MIR value	Glosses: ~12% Flats: ~13% Metallics: ~13% Glosses: 0.86, cannot exceed 0.95 Clear: 0.77, cannot exceed 0.85	*At 7 F, 50% humidity, 1.5 mil thickness		
HAPs content Storage Temperat		** Curing/Recoat time is extended with multiple coats and excessively thick coats **		
Application Tempe Gasoline Resistance Heat Resistance Resin System Shelf life		Gloss*:	High Gloss, >80 Semi-Gloss, 40-50 Flat, <15 Metallic—Not Applicable	
		*as measured on a 60 degree gloss meter		

Available Colors:

<u>Part #</u>	Description	UPC Code	<u>Part #</u>	Description	UPC Code
98-1	Aluminum	043281002356	98-31	Gloss Clear Acrylic	043281002578
98-5	Gold	043281002394	98-32	Dull Aluminum	043281002585
98-14	Copper	043281002455	98-38	Semi-Gloss Black Lacquer	043281002639
98-17	Nickel	043281002486	98-41	Chrome Aluminum	043281002653
98-18	Gloss Black Lacquer	043281002493	98-50	Gold	043281002721
98-30	Flat Black Lacquer	043281002561			

12-19-2021

Seymour of Sycamore | 917 Crosby Avenue | Sycamore |L 60178 Phone | 815.895.9101 • 800.435.4482 Fax | 815.895.8475 • 800.343.4258