Printing date 01/04/2023 Revised On 01/04/2023

### 1 Identification of the substance and manufacturer

Trade name: LIGHT BLUE STRIPE

Product code: 0000160659

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier: 917 Crosby Avenue

Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:** 

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

# 2 Hazard(s) identification

#### Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. H351 Suspected of causing cancer. Route of exposure: Inhalation. Carcinogenicity 2

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 







GHS02 GHS04 GHS07 GHS08

Signal word Danger

**Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Suspected of causing cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 Composition/information on ingredients

Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:				
64742-89-8	VM&P Naphtha		15-25%	
	propane		10-15%	
1317-65-3	Calcium Carbonate		5-10%	
	n-butane		5-10%	
	titanium dioxide		1-5%	
64742-47-8	Mineral Spirits		1-5%	
1330-20-7	xylene (mix)		1-5%	
Additional information: Fo		For the wording of the listed risk phrases refer to section 3.	·	

### 4 First-aid measures

Supply fresh air; consult doctor in case of complaints. After inhalation:

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact: Rinse opened eye for several minutes under running water. Then consult a doctor. After eve contact:

Rinse out mouth and then drink plenty of water. After swallowing: Rinse mouth with water. Do not induce vomiting

Most important symptoms and

effects:

Dizziness

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 01/04/2023 Revised On 01/04/2023

Trade name: LIGHT BLUE STRIPE

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:

Special hazards:

Protective equipment for firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills

with inert absorbent material. Refer to section 13 for disposal information.

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

### 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV (USA) Short-term value: 1000 ppm

(EX)

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm REL (USA) Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm

BEI, A4

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine Medium: urine Time: end of shift

Parameter: Methylhippuric acids

Keep away from foodstuffs and animal feed. Wash hands after use. **Hygienic protection:** 

Immediately remove all soiled and contaminated clothing. Wash hands after use.

Avoid contact with the skin. Avoid contact with the eyes and skin.

Do not eat or drink while working.

Use suitable respiratory protective device in case of insufficient ventilation.

A respirator is generally not necessary when using this product outdoors or in large open areas. In **Breathing equipment:** 

cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

### 9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/04/2023 Revised On 01/04/2023

Trade name: LIGHT BLUE STRIPE

Melting point/Melting range Undetermined.

Boiling point: -44 °C (-47.2 °F)

Flash point: -19 °C (-2.2 °F)

Flammability (solid, gas): Extremely flammable.

**Decomposition temperature:** Not determined.

**Auto igniting:** Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density

Evaporation rate
Partition coefficient: n-octonal/water:

Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

**Possibility of hazardous reactions:** No dangerous reactions known.

Incompatible materials: No further relevant information available.

Hazardous decomposition: No dangerous decomposition products known.

### 11 Toxicological information

LD/LC50 values that are relevant for classific	ation:	
13463-67-7 titanium dioxide		

	10-100 07 7 tituliiuiii uloxiuo				
	Oral	LD50	>20,000 mg/kg (rat)		
	Dermal	LD50	>20,000 mg/kg (rat) >10,000 mg/kg (rbt)		
	Inhalative	LC50/4 h	>6.82 mg/l (rat)		

1330-20-7 xylene (mix)

Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative		6.350 mg/l (rat)

Information on toxicological effects: No data available.

**Skin effects:** Irritant to skin and mucous membranes.

**Eye effects:** No irritating effect.

Sensitization: No sensitizing effects known.

### 12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information: Product does not contain CFC's.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

**Bioaccumulative potential:**Mobility in soil:
Other adverse effects:
No further relevant information available.
No further relevant information available.
No further relevant information available.

#### 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

 UN-Number
 UN1950

 DOT
 UN1950

 UN1950
 UN1950

**DOT** Aerosols, flammable

(Contd. on page 4)

(Contd. of page 3)

## **Safety Data Sheet**

Printing date 01/04/2023 Revised On 01/04/2023

Trade name: LIGHT BLUE STRIPE

1950 Aerosols ADR

Transport hazard class(es):

2.1 Gases Class No

Marine pollutant:

Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ŭ

Packaging Group: UN "Model Regulation": UN1950, Aerosols, 2.1

### 15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

**Toxic Substances Control Act** 

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

1330-20-7 xylene (mix)

16 Other information

Contact: Regulatory Affairs