Safety Data Sheet 1 Identification of the substance and manufacturer Trade name: **ORANGE FLUORESCENT****** Product code: 0000160657 Recommended use: Paint and coatings application. Uses advised against: Any that differs from the recommended use. Seymour of Sycamore Seymour of Sycamore Manufacturer/Supplier: 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com www.seymourpaint.com 1-800-255-3924 **Emergency telephone number:** 2 Hazard(s) identification Classification of the substance or mixture Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. H360 May damage fertility or the unborn child. Toxic to Reproduction 1B Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation. Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. Additional information: **GHS Hazard pictograms** GHS02 GHS04 GHS07 GHS08 Signal word Danger Extremely flammable aerosol. Hazard statements Contains gas under pressure; may explode if heated. May damage fertility or the unborn child. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. **Precautionary statements**

	Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international re	egulations.		
3 Composition/information on ingredients				
	Chemical characterization: Mixtures Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.			
Dangerous	components:			
64742-89-8	VM&P Naphtha	15-25%		
74-98-6	propane	10-15%		
1317-65-3	Calcium Carbonate	5-10%		
106-97-8	n-butane	5-10%		
108-88-3	Toluene	1-5%		
64742-47-8	Mineral Spirits	1-5%		

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

4 First-aid measures		
After inhalation: After skin contact: After eye contact: After swallowing:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.	
Most important symptoms and effects: Indication of any immediate medical	Dizziness	
attention needed:		
5 Fire-fighting measures		
Extinguishing agents: Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.	
•		(Contd. on page 2

F

L

Revised On 01/04/2023

Page 2/4

Printing date 01/04/2023 Revised On 01/04/2023			
Trade name: ORANGE FLUORESCENT***	*		
Protective equipment for firefighters:	(Contd. of page 1) A respiratory protective device may be necessary.		
6 Accidental release measures			
Personal precautions, protective equipment and emergency procedures: Methods and material for containment and cleaning up:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. Ensure adequate ventilation. Dispose contaminated material as waste according to section 13.		
7 Handling and storage Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.		
8 Exposure controls/personal pr	otection		
<u> </u>	t require monitoring at the workplace:		
74-98-6 propane	····		
PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) see Appendix F Minimal oxygen content (D, EX)			
106-97-8 n-butane REL (USA) Long-term value: 1900 r	ma/m ³ 800 ppm		
TLV (USA) Short-term value: 1000 (EX) 108-88-3 Toluene			
PEL (USA) Long-term value: 200 pr	pm		
PEL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s	hift		
REL (USA) Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm TLV (USA) Long-term value: 20 ppm			
BEI, OTO, A4			
Ingredients with biological limit v	alues:		
108-88-3 Toluene			
BEI (USA) 0.02 mg/L Medium: blood Time: prior to last shift o Parameter: Toluene 0.03 mg/L Medium: urine	f workweek		
Time: end of shift Parameter: Toluene			
0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with	n hydrolysis (background)		
Hygienic protection: Breathing equipment:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In		
Hand protection:	cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine. Nitrile gloves.		
Eye protection:	The glove material must be impermeable and resistant to the substance. Tightly sealed goggles		
9 Physical and chemical propert	ies		
Appearance: Aerosol. (Contd. on page			

Ļ

Revised On 01/04/2023

Trade name: ORANGE FLUORESCENT****				
(Contd. of page 2)				
Odor: Odor threshold:	Aromatic Not determined.			
pH-value:	Not determined.			
Melting point/Melting range Boiling point:	Undetermined. -44 °C (-47.2 °F)			
Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.			
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not self-igniting.			
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol %			
Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/wate	Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. r: Not determined.			
Solubility: Viscosity: Water:	Not determined. Not determined. 33.5 %			
10 Stability and reactivity Reactivity:	Stable at normal temperatures.			
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.			
Chemical stability: Possibility of hazardous reactions: Incompatible materials:	Not fully evaluated. No dangerous reactions known. No further relevant information available.			
Hazardous decomposition:	No dangerous decomposition products known.			
11 Toxicological information				
Information on toxicological effects				
Skin effects: Eye effects:	Irritant to skin and mucous membranes. No irritating effect.			
Sensitization:	No sensitizing effects known.			
12 Ecological information				
Aquatic toxicity:	Hazardous for water, do not empty into drains.			
Persistence and degradability: Other information:	The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.			
Bioaccumulative potential: Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available. No further relevant information available.			
13 Disposal considerations Dispose of in accordance with local, si	tate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be			
	r cut empty containers with electric or gas torches. Completely empty cans should be recycled. Water, if necessary with cleansing agents.			
14 Transport information				
UN-Number	UN1950			
DOT	UN1950 UN1950			
DOT ADR	Aerosols, flammable 1950 Aerosols			
Transport hazard class(es):				
Class Marine pollutant:	2.1 Gases No			
Special precautions for user: EMS Number:	Warning: Gases F-D,S-U			
Packaging Group:	1			
	(Contd. on page 4)			

Page 4/4

Trade name: ORANGE FLUORESCENT****

UN "Model Regulation":

UN1950, Aerosols, 2.1

(Contd. of page 3)

15 Regulatory information				
SARA Section 355 (extremely hazardous substances):				
None of the ingredients in this p	None of the ingredients in this product are listed. SARA Section 313 (Specific toxic chemical listings):			
SARA Section 313 (Specific to				
108-88-3 Toluene				
Toxic Substances Control Act (TSCA): Canadian Domestic Substanc	All hazardous ingredients are found on the inventory list of substances.			
(DSL):	All ingredients are listed or exempted.			
Consumer Product Safety Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.			
	micals known to cause cancer:			
None of the ingredients in this p	roduct are listed.			
Prop 65 chemicals known to cause birth defects or reproductive harm:				
108-88-3 Toluene	108-88-3 Toluene			
EPA:				
None of the ingredients is listed.				
16 Other information				
Contact:	Regulatory Affairs			