



ECONO MARK

An economically priced marking paint that has a water base formulation which results in a highly visible permanent mark. Special spray head for writing, spot marking or line marking.

Suggested Uses:

Forestry
 Petrochemical
 Mining
 Lumber
 Screen enclosures

Packaging:

Cans per case	12
Shipping weight per case	12 lbs.
Container	16 fluid ounce can
Label weight	11 ounces (312 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	18%
MIR value	0.78, cannot exceed 0.95
HAPs content	19%
Storage Temperature	40-90F
Application Temperature	50-100F
Durability	Good
Abrasion Resistance	Good
Heat Resistance	250F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch	10 minutes
To handle	45 minutes

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree
 gloss meter

Available Colors:

Part #	Description	UPC Code
16-2002	White	043281001199
16-2003	Black	043281001205
16-2004	Red	043281001212
16-2034	Yellow	043281001229
16-2035	Blue	043281001236
16-2088	Green	043281001243

12-1-2021