Printing date 01/15/2024 Revised On 01/15/2024

1 Identification

Trade name: **PURPLE** 0000200680 Product code:

Paint and coatings application. Recommended use:

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Seymour of Sycamore

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA

phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. H351 Suspected of causing cancer. Route of exposure: Inhalation. Carcinogenicity 2

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms







GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard-determining components of

labeling:

Calcium Carbonate

Toluene

titanium dioxide

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Suspected of causing cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use. **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Physical dangers:

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the

contents may be harmful or fatal.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

			The product to a mixture of the observations noted bottom man included additional	
Dangerous components:				
647	742-89-8	VM&P Naphtha		15-25%
	74-98-6	propane		10-15%
13	317-65-3	Calcium Carbonate		5-10%
		n-butane		5-10%
647	742-47-8	Mineral Spirits		1-5%
		xylene (mix)		1-5%
134	163-67-7	titanium dioxide		1-5%

4 First-aid measures

Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/15/2024 Revised On 01/15/2024

Trade name: PURPLE

Rinse opened eye for several minutes under running water. Then consult a doctor. After eye contact: After swallowing: Rinse mouth with water. Do not induce vomiting.

Information for doctor: Most important symptoms and

effects: Indication of any immediate medical

Dizziness

No further relevant information available.

5 Fire-fighting measures

attention needed:

Extinguishing media

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

Special hazards: Protective equipment for firefighters:

Additional information

A respiratory protective device may be necessary. Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Environmental precautions: Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Do not allow product to reach sewage systems or ground water.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Fire/explosion protection:

Use only in well ventilated areas.

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from

electrostatic discharges.

Conditions for safe storage:

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that

require monitoring at the

workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other

recommended exposure limit.

At this time, the other constituents have no known exposure limits.

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm REL Long-term value: 1800 mg/m³, 1000 ppm TLV see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL Long-term value: 1900 mg/m³, 800 ppm

TLV Short-term value: 1000 ppm (EX)

1330-20-7 xylene (mix)

PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

BEI, A4

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

Exposure controls

Immediately remove all soiled and contaminated clothing. Hygienic protection:

Wash hands after use. Avoid contact with the skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/15/2024 Revised On 01/15/2024

Trade name: PURPLE

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

General Information:

Appearance:
Odor:
Odor threshold:

PH-value:
Melting point/Melting range
Boiling point:

Flash point:

Aerosol.
Aromatic
Not determined.
Undetermined.
-44 °C (-47.2 °F)

-19 °C (-2.2 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120

degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % Upper Explosion Limit: 10.9 Vol %

Vapor pressure:40 PSI2750 hPaVapor Pressure:40 PSI, 2750 hPa

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density
Evaporation rate
Partition coefficient: n-octonal/water: Not determined.
Solubility:
Viscosity:
Dynamic:
Not determined.

Water: 33.9 %

10 Stability and reactivity

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid
Incompatible materials:
Hazardous decomposition:

No further relevant information available.
No further relevant information available.
No dangerous decomposition products known.

11 Toxicological information

The following the first the first term and the firs							
LD/LC50 values that are relevant for classification:							
1330-20-7 xylene (mix)							
Oral	LD50	8,700 mg/kg (rat)					
Dermal	LD50	2,000 mg/kg (rbt)					
Inhalative	LC50/4 h	6,350 mg/l (rat)					
13463-67-7 titanium dioxide							
Oral	LD50	>20,000 mg/kg (rat)					
Dermal	LD50	>10,000 mg/kg (rbt)					

Inhalative LC50/4 h >6.82 mg/l (rat)

Skin effects: Irritant to skin and mucous membranes.

Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

IARC (International Agency for Research on Cancer)

1330-20-7 xylene (mix) 3 13463-67-7 titanium dioxide 2B

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: Hazardous for water, do not empty into drains.

(Contd. on page 4)

Printing date 01/15/2024 Revised On 01/15/2024

Trade name: PURPLE

(Contd. of page 3) Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

Bioaccumulative potential: No further relevant information available. No further relevant information available. Mobility in soil:

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Waste treatment methods

Completely empty cans should be recycled. Recommendation: Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT UN1950

UN proper shipping name:

Aerosols, flammable DOT

Transport hazard class(es):

2.1 Gases Class Special precautions for user: Warning: Gases F-D,S-U

EMS Number:

DOT

Packaging Group:

15 Regulatory information

Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Consumer Product Safety

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead mission (CDSC)

	Comission	(CF3C). This product complies with 10 CF1 1303 and does not contain more than 30 ppm of lead.
	Hazardous	Air Pollutants
	1330-20-7	rylene (mix)
	108-88-3	Foluene
	100-41-4	ethyl benzene
	136-52-7	cobalt bis(2-ethylhexanoate)

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide 100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA: 1330-20-7 xylene (mix)

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Obtain special instructions before use. **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

A Chemical Safety Assessment has not been carried out. Chemical safety assessment:

Τ

Safety Data Sheet acc. to OSHA HCS

Printing date 01/15/2024 Revised On 01/15/2024

Trade name: PURPLE

(Contd. of page 4)

16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

01/15/2024 Date of preparation / last revision

IMDG: International Maritime Code for Dangerous Goods Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
REL: Recommended Exposure Limit
Flammable Aerosols 1: Aerosols – Category 1
Gases under Pressure - Liquefied gas: Gases under pressure – Liquefied gas
Carcinogenicity 2: Carcinogenicity – Category 2
Toxic to Reproduction 1B: Reproductive toxicity – Category 1B
Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2