

TECHNICAL DATA SHEET



BLACK WRINKLE PAINT #16-2448

Seymour's black wrinkle paint can reproduce the original factory finish on a variety of car and truck parts. This durable black coating resists gasoline, automotive fluids, fading, rust, corrosion, and chipping. It has excellent hiding qualities and can be used where conventional coatings break down.

Suggested Uses:

Metal dashboards
Ignition wire holders
Valve covers
Gun stocks
Beautify motorcycle engines
Tool handles for better grip

Packaging:

UPC Code 043281001281

Cans per case 6 Shipping weight per case 7 lbs.

Container 16 fluid ounce can
Label weight 12 ounces (340 grams)
Shipping Classification limited quantity, UN 1950

Hazard Class 2.1

Properties:

Coverage Up to 7 square feet
Cleanup Lacquer or paint thinner
Flammability Extremely Flammable

Flash point -4F Specific Gravity 0.80 Solids Content 26%

MIR value 0.92, cannot exceed 0.95

Storage Temperature 40-90F
Application Temperature 50-100F
Abrasion Resistance Very Good
Heat Resistance 250F
Gasoline Resistance Yes

Resin System Linseed and Tung Oil Shelf life Guaranteed for 2 years

Food contact rating No

Dry Time:

To touch 30 minutes
8 hours is required to complete
the wrinkling process

Gloss: Varies with pattern

Additional Information:

Two medium coats are needed to achieve the wrinkled texture, with the second coat applied approximately three minutes after the first. The wrinkling effect does not appear right away. Allow eight hours to cure.

12-2-2021