Printing date 01/25/2024 Revised On 01/25/2024

1 Identification of the substance and manufacturer

Trade name: STAINLESS STEEL CLEANER AND POLISH

0000200027 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Additional information: **GHS Hazard pictograms**

Signal word Warning

Contains gas under pressure; may explode if heated. **Hazard statements** Protect from sunlight. Store in a well-ventilated place. **Precautionary statements**

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description:

Dangerous components:				
74-98-6	propane	1-5%		
106-97-8	n-butane	1-5%		
111-76-2	Glycol Ether EB	0.2-1%		

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

Rinse opened eye for several minutes under running water. After eye contact:

Rinse mouth with water. Do not induce vomiting. After swallowing:

Most important symptoms and

Dizziness effects:

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: No further relevant information available.

Protective equipment for

firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for

Use respiratory protective device against the effects of fumes/dust/aerosol.

containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Storage requirements:

Store lockéd up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

(Contd. on page 2)

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: STAINLESS STEEL CLEANER AND POLISH

TLV (USA) | see Appendix F Minimal oxygen content (D, EX) (Contd. of page 1)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) | Short-term value: 1000 ppm

(EX)

111-76-2 Glycol Ether EB

PEL (USA) Long-term value: 240 mg/m³, 50 ppm

Skin

REL (USA) Long-term value: 24 mg/m³, 5 ppm

Skin

TLV (USA) Long-term value: 20 ppm

BEI, A3

Ingredients with biological limit values:

111-76-2 Glycol Ether EB

BEI (USA) 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

Hygienic protection: Wash hands after use

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Not required.

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic

Odor threshold:

pH-value:

Melting point/Melting range

Not determined.

Undetermined.

Melting point/Melting range Boiling point:Undetermined.
36 °C (96.8 °F)

Flash point: Not applicable, as aerosol.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion:
Lower Explosion Limit:
Upper Explosion Limit:
Not determined.
Not determined.

Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. Not determined.

Water: 83.4 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known. Incompatible materials: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 v:	alues that ar	e relevant fo	or classification:

11	1	-76.	.2	Gl	vcol	Eth	۱er	FF

Oral LD50 1,200 mg/kg (ATE) 1,480 mg/kg (rat)

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: STAINLESS STEEL CLEANER AND POLISH

Dermal LD50 400 mg/kg (rab) Inhalative LC50/4 h 3 mg/l (ATE)

Information on toxicological effects: No data available. No irritant effect. No irritating effect.

Eye effects: No sensitizing effects known. Sénsitization:

12 Ecological information

Skin effects:

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes. Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

No further relevant information available. Bioaccumulative potential: Mobility in soil: No further relevant information available. No further relevant information available. Other adverse effects:

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, non-flammable ADR 1950 AEROSOLS

Transport hazard class(es):

Class 2.2 Gases Warning: Gases Special precautions for user:

EMS Number: F-D,S-Ŭ

Packaging Group:

UN "Model Regulation": UN 1950 AEROSOLS, 2.2

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

None of the ingredients is listed.

16 Other information

Contact: Regulatory Affairs