





BRAAP RUST CONVERTER AND PRIMER #BW16-45

Rust Converter and primer can be applied to any iron or steel surface to penetrate rust and turn it into a protective black coating. This protective coating will be resistant to moisture and prevents future rust growth. Just remove any loose rust, then apply it like a primer to rusted surfaces. Greatly reduces time spent wire brushing and sanding. Durable and tough, it can be left as is, but is also compatible with most top coats.

Suggested Uses:

Frames **Trailers** Control arms Roll cages **Axles** Sheet metal

Packaging:

UPC Code 043281009294 Cans per case

9 lbs. Shipping weight per case

Container 16 fluid ounce can Label weight 12 ounces (340 grams) Shipping Classification limited quantity, UN 1950 2.1

Hazard Class

Properties:

Solids Content

Coverage Up to 12 square feet Cleanup Paint or lacquer thinner Flammability Extremely Flammable Flash point -2 F Specific Gravity 0.80

0.69, cannot exceed 0.70 MIR value

30%

Storage Temperature 40-100F **Application Temperature** 50-90F Gasoline Resistance Yes Heat Resistance 250 F

Chain Stopped Alkyd Resin System Shelf life Guaranteed for 2 years

Dry Time*:

10 minutes To touch 24 hours To recoat/topcoat

*At 72F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

12-2-2021

