

# **TECHNICAL DATA SHEET**



# STRIPE TEMPORARY MARKING PAINT

A patented temporary marking paint that dries fast and produces vivid lines. Marking paint is water soluble and can be removed immediately with a garden hose or gradually after a few rains. Covers approximately 400 linear feet per can. The sprayhead can be actuated by hand or with the #Z-606 Marking Wand or #Z-605 Marking Gun. VOC compliant.

# **Suggested Uses:**

Golf courses Utilities Sporting events Landscaping Surveying Playgrounds

## Packaging:

Cans per case Shipping weight per case Container Label weight Shipping Classification Hazard Class 12 20 lbs. 20 fluid ounce can 16 ounces (454 grams) limited quantity, UN 1950

2.1

## **Properties:**

Cleanup Soap and water
Flammability Extremely Flammable

Flash point -4F Specific Gravity 0.83 Solids Content 22%

MIR value 0.61, cannot exceed 0.85

HAPs content 3%
Storage Temperature 40-100F
Application Temperature 50-90F
Durability Poor
Abrasion Resistance Good
Heat Resistance 250F

Shelf life Guaranteed for 2 years

Trade Secret

## **Dry Time\*:**

To touch 20 minutes

\*At 72<sub>0</sub> F, 50% humidity, 1.5 mil thickness

\*\*Curing/Recoat time is extended with multiple coats and excessively thick coats\*\*

Gloss\*: Flat, <15

\*as measured on a 60 degree gloss meter

## **Available Colors:**

Resin System

Part # Description UPC Code

20-633 White 043281006392

12-7-2021