Printing date 01/25/2024 Revised On 01/25/2024

1 Identification of the substance and manufacturer

Trade name: **MARINE PAINT & GELCOAT POLISH**

0000902019 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:


GHS Hazard pictograms

Precautionary statements









Signal word

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
64742-47-8	Mineral Spirits	25-50%
74-98-6	propane	5-10%
106-97-8	n-butane	1-5%
8042-47-5	White mineral oil, petroleum	1-5%
7632-00-0	sodium nitrite	0.2-1%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. After eye contact: Rinse mouth with water. Do not induce vomiting.

After swallowing: Most important symptoms and

Dizziness effects:

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: No further relevant information available. Protective equipment for

firefighters: A respiratory protective device may be necessary. Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: MARINE PAINT & GELCOAT POLISH

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective

equipment and emergency

procedures: Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

Hand protection:

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm

(EX)

Hygienic protection: Wash hands after use.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection:

Not required.

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic

Odor threshold:

PH-value:

Melting point/Melting range

Not determined.

Undetermined.

Boiling point: -44.5 °C (-48.1 °F)

Flash point: -19 °C (-2.2 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion:Not determined.Lower Explosion Limit:Not determined.Upper Explosion Limit:Not determined.Vapor pressure:Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density

Evaporation rate
Partition coefficient: n-octonal/water: Not determined.
Solubility:
Viscosity:

Not determined.
Not determined.
Not determined.

Water: 54.5 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability:

Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials:
Hazardous decomposition:

No further relevant information available.
No dangerous decomposition products known.

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: MARINE PAINT & GELCOAT POLISH

(Contd. of page 2)

11 Toxicological information

Information on toxicological effects: No data available. No irritant effect. Skin effects: Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

Bioaccumulative potential: No further relevant information available. No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable 1950 AEROSOLS **ADR**

Transport hazard class(es):

Class 2.1 Gases Special precautions for user: Warning: Gases

F-D,S-Ŭ **EMS Number:**

Packaging Group:

UN "Model Regulation": **UN 1950 AEROSOLS, 2.1**

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed. **Toxic Substances Control Act**

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

None of the ingredients is listed.

16 Other information

Contact: Regulatory Affairs