Printing date 01/09/2024 Revised On 01/09/2024

#### 1 Identification of the substance and manufacturer

Trade name: SAFETY BLUE Product code: 0006201427

**Recommended use:** Paint and coatings application.

**Uses advised against:** Any that differs from the recommended use.

Manufacturer/Supplier: Seymour of Sycamore 917 Crosby Avenue

Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: 1-800-255-3924

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

#### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms







GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 3 Composition/information on ingredients

Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

	ood iption				
Dangerous components:					
67-64-1	Acetone	15-25%			
74-98-6	propane	15-25%			
	n-butane	5-10%			
	barium sulfate	5-10%			
	Isobutyl Acetate	5-10%			
	Glycol Ether EP	≥5-<10%			
	titanium dioxide	1-5%			
	butyl acetate	1-5%			
	Methyl Propyl Ketone	1-5%			
108-10-1	methyl isobutyl ketone	1-5%			

#### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Contd. on page 2)

(Contd. of page 1)

Printing date 01/09/2024 Revised On 01/09/2024

Trade name: SAFETY BLUE

After swallowing: Rinse out mouth and then drink plenty of water.

Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

**Extinguishing agents:** Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

Protective equipment for

firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for

containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

#### 8 Exposure controls/personal protection

Components	with limit	values	tnat r	equire	monitori	ng at t	ne work	piace:

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV (USA) Short-term value: 500 ppm

Long-term value: 250 ppm A4, BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm

(EX)

## 7727-43-7 barium sulfate

PEL (USA) Long-term value: 15\* 5\*\* mg/m³ \*total dust \*\*respirable fraction

REL (USA) Long-term value: 10\* 5\*\* mg/m³ \*total dust \*\*respirable fraction

TLV (USA) Long-term value: 5\* mg/m³ \*inhalable fraction; E

110-19-0 Isobutyl Acetate

PEL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppm

REL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppm

TLV (USA) Short-term value: 150 ppm Long-term value: 50 ppm

## 123-86-4 butyl acetate

PEL (USA) Long-term value: 710 mg/m³, 150 ppm

REL (USA) Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm

TLV (USA) Short-term value: 150 ppm Long-term value: 50 ppm

## 107-87-9 Methyl Propyl Ketone

PEL (USA) Long-term value: 700 mg/m³, 200 ppm

REL (USA) Long-term value: 530 mg/m<sup>3</sup>, 150 ppm

TLV (USA) Short-term value: 150 ppm

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/09/2024 Revised On 01/09/2024

Trade name: SAFETY BLUE

108-10-1 methyl isobutyl ketone

PEL (USA) Long-term value: 410 mg/m³, 100 ppm

REL (USA) Short-term value: 300 mg/m³, 75 ppm

Long-term value: 205 mg/m³, 50 ppm

TLV (USA) | Short-term value: 75 ppm | Long-term value: 20 ppm

BEI, A3

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

**Hygienic protection:** Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance. **Eye protection:** Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.

Odor:
Odor threshold:

PH-value:
Melting point/Melting range
Boiling point:

Flash point:

Aromatic
Not determined.
Undetermined.
-44 °C (-47.2 °F)
-19 °C (-2.2 °F)

Flammability (solid, gas): Extremely flammable.

**Decomposition temperature:** Not determined.

**Auto igniting:** Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density

Evaporation rate
Partition coefficient: n-octonal/water:

Not determined.

Water: 0.0 %

10 Stability and reactivity

**Reactivity:** Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability:

Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials:
Hazardous decomposition:

No dangerous reactions known.

No further relevant information available.

No dangerous decomposition products known.

Safety Data Sheet

Printing date 01/09/2024 Revised On 01/09/2024

Trade name: SAFETY BLUE

(Contd. of page 3)

## 11 Toxicological information

LD/LC50 values that are relevant for classification:						
110-19-0 I	110-19-0 Isobutyl Acetate					
Oral	LD50	4,763 mg/kg (rbt)				
13463-67-	13463-67-7 titanium dioxide					
Oral	LD50	>20,000 mg/kg (rat)				
Dermal	LD50	>10,000 mg/kg (rbt)				
Inhalative	Inhalative LC50/4 h >6.82 mg/l (rat)					
123-86-4 butyl acetate						
-		14,000 mg/kg (rat)				
Inhalative	Inhalative LC50/4 h >21 mg/l (rat)					
108-10-1 methyl isobutyl ketone						
Oral	LD50	2,100 mg/kg (rat)				
	LD50	16,000 mg/kg (rab)				
Inhalative	LC50/4 h	11 mg/l (ATE)				
		8.3-16.6 mg/l (rat)				

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

No further relevant information available. Bioaccumulative potential: No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

**UN-Number** UN1950 DOT UN1950

DOT Aerosols, flammable ADR 1950 Aerosols

Transport hazard class(es):

2.1 Gases Class Marine pollutant: No Warning: Gases Special precautions for user:

**EMS Number:** F-D,S-U

Packaging Group: UN "Model Regulation": **UN 1950 AEROSOLS, 2.1** 

## 15 Regulatory information

#### SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

## SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

108-10-1 methyl isobutyl ketone

**Toxic Substances Control Act** 

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

(Contd. on page 5)

## **Safety Data Sheet**

Printing date 01/09/2024 Revised On 01/09/2024

Filling date 01/09/2024		Nevised Off 01/09/2024				
Trade name: SAFETY BLUE						
		(Contd. of page 4)				
California Proposition 65 chemical	s known to cause cancer:					
13463-67-7 titanium dioxide						
108-10-1 methyl isobutyl ketone						
100-41-4 ethyl benzene						
Prop 65 chemicals known to cause	Prop 65 chemicals known to cause birth defects or reproductive harm:					
108-10-1 methyl isobutyl ketone	108-10-1 methyl isobutyl ketone					
EPA:						
67-64-1 Acetone		I				
7727-43-7 barium sulfate		D, CBD(inh), NL(oral)				
110-19-0 Isobutyl Acetate		D				
108-10-1 methyl isobutyl ketone		I				
USDA (United States Department of Agriculture):  Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of the product to be safe for use in official meat and poultry establishments, and to perform well under daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of the product to be safe for use in official meat and poultry establishments, and to perform well under may be used where there is a possibility of incidental food contact.						

# 16 Other information Contact:

Contact: Regulatory Affairs