1 Identification of the substance and manufacturer

1 Identification of the substance and manufacturer			
Trade name:	GLOSS MEDIUM BLUE		
Product code: Recommended use: Uses advised against: Manufacturer/Supplier:	GLOSS MEDIUM BLUE0000980035Paint and coatings application.Any that differs from the recommended use.Seymour of Sycamore917 Crosby Avenue917 Crosby AvenueSycamore, IL 60178 USAphone: 815-895-9101www.seymourpaint.comwww.seymourpaint.com		
Emergency telephone number:	1-800-255-3924		
2 Hazard(s) identification			
Classification of the substance or m	ixture		
Flammable Aerosols 1	H222 Extremely flammable aerosol.		
Gases under Pressure - Liquefied gas	H280 Contains gas under pressure; ma	y explode if heated.	
Eye Irritation 2A	H319 Causes serious eye irritation.		
Carcinogenicity 2	H351 Suspected of causing cancer. Rou	ute of exposure: Inhalation.	
Toxic to Reproduction 1B	H360 May damage fertility or the unborn		
Specific Target Organ Toxicity - Single			
	ted Exposure 2 H373 May cause damage to organs thro	ough prolonged or repeated exposure.	
Additional information:			
GHS Hazard pictograms			
	GHS02 GHS04 GHS07 GHS08		
Signal word Hazard statements	Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of causing cancer. Route of exposure: Inhala May damage fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or rep		
Precautionary statements	 Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations. 		
3 Composition/information on ingredients			
Chemical characterization: Mixtures			

Chemical C	haracterization: Mixture	es This product is a mixture of the substances listed below with nonhazardous additions.	
Dangerous	components:		
67-64-1	Acetone		25-50%
	propane		15-25%
64742-89-8	VM&P Naphtha		10-15%
	n-butane		10-15%
64742-47-8	Mineral Spirits		5-10%
108-88-3	Toluene		1-5%
13463-67-7	titanium dioxide		1-5%
67-63-0	Isopropyl Alcohol		1-5%

- **4 First-aid measures**
 - After inhalation: After skin contact: After eye contact:

Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 2)

Safety Data Sheet

Printing date 01/17/2024

Revised On 01/17/2024

A free and a line of	Contd. of pag
After swallowing:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medi attention needed:	cal No further relevant information available.
Fire-fighting measures	
Extinguishing agents: Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.
Protective equipment for firefighters:	A respiratory protective device may be necessary.
Accidental release measures	
Personal precautions, protective	
equipment and emergency	Wear protective equipment. Keen upprotected across a succe
procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Ensure adequate ventilation.
	Dispose contaminated material as waste according to section 13.
Handling and storage	
Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p	ng/m³, 250 ppm pm
PEL (USA) Long-term value: 2400 n REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane	ng/m³, 250 ppm pm pm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 p	ng/m³, 250 ppm pm pm mg/m³, 1000 ppm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEl 74-98-6 propane	ng/m³, 250 ppm pm pm mg/m³, 1000 ppm mg/m³, 1000 ppm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) PEL (USA) Long-term value: 1800 n REL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane Non-term	ng/m³, 250 ppm pm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX)
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm
REL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pLong-term value: 250 pA4, BEI74-98-6 propaneLong-term value: 1800 nPEL (USA)Long-term value: 1800 nTLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900 nTLV (USA)Short-term value: 1900 nTLV (USA)Short-term value: 1000 n	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1900 n TLV (USA) Short-term value: 1000 n (EX)	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1000 n TLV (USA) Long-term value: 1000 n TLV (USA) Long-term value: 200 p CEL (USA) Long-term value: 200 p Ceiling limit value: 300;	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1000 n TLV (USA) Short-term value: 1000 n TLV (USA) Long-term value: 200 p CEV (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 500 p Long-term value: 250 p 74-98-6 propane PEL (USA) PEL (USA) Long-term value: 1800 n TLV (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1900 n TLV (USA) Short-term value: 200 p (EX) Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 560 n Long-term value: 560 n Long-term value: 375 m	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift ng/m³, 150 ppm ig/m³, 100 ppm
REL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pLong-term value: 500 pLong-term value: 250 p74-98-6 propanePEL (USA)Long-term value: 1800 nREL (USA)Long-term value: 1800 nTLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)Long-term value: 1900 nTLV (USA)Short-term value: 1900 nTLV (USA)Short-term value: 1000 nPEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 pp	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift ng/m³, 150 ppm ig/m³, 100 ppm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1000 n (EX) 108-88-3 Toluene PEL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 375 m TLV (USA) Long-term value: 20 pp BEI, OTO, A4	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift ng/m³, 150 ppm ig/m³, 100 ppm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n REL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1900 n TLV (USA) Long-term value: 1000 n (EX) 108-88-3 Toluene PEL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 375 m TLV (USA) Long-term value: 20 pp BEI, OTO, A4 67-63-0 Isopropyl Alcohol PEL (USA) Long-term value: 980 m	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift ng/m³, 150 ppm m m
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n REL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1000 n (EX) 108-88-3 Toluene PEL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 375 m TLV (USA) Long-term value: 20 pp BEI, OTO, A4 67-63-0 Isopropyl Alcohol PEL (USA) Long-term value: 980 m REL (USA) Short-term value: 980 m REL (USA) Short-term value: 980 m REL (USA) Short-term value: 1225	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift ng/m³, 150 ppm ng/m³, 150 ppm mg/m³, 500 ppm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n REL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1900 n TLV (USA) Long-term value: 1900 n TLV (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Long-term value: 375 m TLV (USA) Short-term value: 20 pp BEI, OTO, A4 67-63-0 Isopropyl Alcohol PEL (USA) Long-term value: 980 m REL (USA) Short-term value: 980 m REL (USA) Short-term value: 1225 Long-term value: 980 m TLV (USA) Short-term value: 400 p	ng/m ³ , 250 ppm pm mg/m ³ , 1000 ppm mg/m ³ , 1000 ppm I oxygen content (D, EX) mg/m ³ , 800 ppm ppm 500* ppm hift ng/m ³ , 150 ppm ng/m ³ , 150 ppm mg/m ³ , 500 ppm mg/m ³ , 500 ppm pm
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n REL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1900 n TLV (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Long-term value: 375 m TLV (USA) Short-term value: 20 pp BEI, OTO, A4 67-63-0 Isopropyl Alcohol PEL (USA) Long-term value: 980 m REL (USA) Short-term value: 980 m REL (USA) Short-term value: 980 m REL (USA) Short-term value: 200 pp BEI, OTO, A4	ng/m ³ , 250 ppm pm mg/m ³ , 1000 ppm mg/m ³ , 1000 ppm I oxygen content (D, EX) mg/m ³ , 800 ppm ppm 500* ppm hift ng/m ³ , 150 ppm ng/m ³ , 150 ppm mg/m ³ , 100 ppm m
REL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pA4, BEI74-98-6 propanePEL (USA)Long-term value: 1800 nREL (USA)Long-term value: 1800 nTLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)Long-term value: 1900 nTLV (USA)Short-term value: 1000 nTLV (USA)Short-term value: 1000 nTLV (USA)Short-term value: 1000 nTLV (USA)Short-term value: 200 pPEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 pBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 1225 Long-term value: 980 mTLV (USA)Short-term value: 200 pBEI, A4Ingredients with biological limit v	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift ng/m³, 150 ppm ng/m³, 150 ppm m m
REL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pA4, BEI74-98-6 propanePEL (USA)Long-term value: 1800 nREL (USA)Long-term value: 1800 nTLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)Long-term value: 1900 nTLV (USA)Short-term value: 1000 nTLV (USA)Short-term value: 1000 nTLV (USA)Short-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 pBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mTLV (USA)Short-term value: 200 pBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Short-term value: 200 pBEI, A4Ingredients with biological limit v67-64-1 Acetone	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift ng/m³, 150 ppm ng/m³, 150 ppm m m
REL (USA)Long-term value: 590 mTLV (USA)Short-term value: 500 pA4, BEI74-98-6 propanePEL (USA)Long-term value: 1800 nREL (USA)Long-term value: 1800 nTLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)Long-term value: 1900 nTLV (USA)Short-term value: 1000 nTLV (USA)Short-term value: 1000 nTLV (USA)Short-term value: 1000 nTLV (USA)Long-term value: 200 pPEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 pBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 980 mTLV (USA)Short-term value: 200 pBEI, A4Ingredients with biological limit v	ng/m³, 250 ppm pm mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hift ng/m³, 150 ppm ng/m³, 150 ppm m m
REL (USA) Long-term value: 590 m TLV (USA) Short-term value: 500 p Long-term value: 250 p A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 n REL (USA) Long-term value: 1800 n TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) Long-term value: 1900 n TLV (USA) Short-term value: 1000 (EX) 108-88-3 Toluene PEL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 300; *10-min peak per 8-hr s REL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Long-term value: 200 p BEI, OTO, A4 67-63-0 Isopropyl Alcohol PEL (USA) Long-term value: 980 m REL (USA) Short-term value: 1225 Long-term value: 980 m TLV (USA) Short-term value: 200 p BEI, A4 Ingredients with biological limit v 67-64-1 Acetone BEI (USA) 25 mg/L	ng/m ³ , 250 ppm pm g/m ³ , 1000 ppm mg/m ³ , 1000 ppm l oxygen content (D, EX) mg/m ³ , 800 ppm ppm 500° ppm hift ng/m ³ , 150 ppm m g/m ³ , 100 ppm m g/m ³ , 400 ppm m g/m ³ , 400 ppm g/m ³ , 400 ppm g/m ³ , 400 ppm g/m ³ , 400 ppm

Revised On 01/17/2024

Trade name: GLOSS MEDIUM BLUE

	(Contd. of page	
108-88-3 Toluene		
BEI (USA) 0.02 mg/L Medium: blood		
Time: prior to last	Time: prior to last shift of workweek	
Parameter: Toluen	e	
0.03 mg/L		
Medium: urine		
Time: end of shift		
Parameter: Toluen	e	
0.3 mg/g creatinin	9	
Medium: urine		
Time: end of shift	ol with hydrolysis (background)	
67-63-0 Isopropyl Alcohol		
BEI (USA) 40 mg/L		
Medium: urine		
	at end of workweek	
Hygienic protection:	e (background, nonspecific) Keep away from foodstuffs and animal feed. Wash hands after use.	
Hygienic protection.	Immediately remove all soiled and contaminated clothing.	
	Wash hands after use.	
	Store protective clothing separately. Avoid contact with the eyes and skin.	
	Do not eat or drink while working.	
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas.	
	cases where short and/or long term overexposure exists, a NIOSH approved respirator should worn. If you suspect overexposure conditions exist, please consult an authority on chemic	
	hygiene.	
Hand protection:	Nitrile gloves.	
	The glove material must be impermeable and resistant to the substance.	
Eve protection:	Tichtly apple dagage	
Eye protection:	Tightly sealed goggles	
Eye protection: Physical and chemical pro	Tightly sealed goggles	
Physical and chemical properties of the second seco	Tightly sealed goggles operties Aerosol.	
Physical and chemical pro Appearance: Odor:	Tightly sealed goggles operties Aerosol. Aromatic	
Physical and chemical pro Appearance: Odor: Odor threshold:	Tightly sealed goggles operties Aerosol. Aromatic Not determined.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value:	Tightly sealed goggles	
Physical and chemical pro Appearance: Odor: Odor threshold:	Tightly sealed goggles operties Aerosol. Aromatic Not determined.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point:	Tightly sealed goggles	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range	Tightly sealed goggles	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point:	Tightly sealed goggles operties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas):	Tightly sealed goggles operties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting:	Tightly sealed goggles operties Aerosol. Aromatic Not determined. Not determined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. : Not determined. Product is not self-igniting.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flash point: Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit:	Tightly sealed goggles Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. : Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol %	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion:	Tightly sealed goggles Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. : Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol %	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure:	Tightly sealed goggles operties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. : Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density:	Tightly sealed goggles operties Aerosol. Aromatic Not determined. Not determined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00)	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate	Tightly sealed goggles Poperties Aerosol. Aromatic Not determined. Undetermined44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density:	Tightly sealed goggles Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. : Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not determined. Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octor Solubility:	Tightly sealed goggles Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. : Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not determined. Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octor Solubility: Viscosity:	Tightly sealed goggles Aerosol. Aromatic Not determined. Undetermined. Undetermined44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. hal/water: Not determined. Not determined. Not determined. Not determined. Not determined.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octor Solubility:	Tightly sealed goggles Poperties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octor Solubility: Viscosity: Water:	Tightly sealed goggles Aerosol. Aromatic Not determined. Undetermined. Undetermined44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. hal/water: Not determined. Not determined. Not determined. Not determined. Not determined.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octor Solubility: Viscosity: Water:	Tightly sealed goggles operties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. hal/water: Not determined. Not	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octor Solubility: Viscosity: Water: Stability and reactivity Reactivity:	Tightly sealed goggles operties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. : Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined.	
Physical and chemical provements of the second structure of the second structu	Tightly sealed goggles poperties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. hal/water: Not determined. Do not warehouse in subfreezint temperatures.	
Physical and chemical pro Appearance: Odor: Odor threshold: pH-value: Melting point/Melting range Boiling point: Flash point: Flash point: Flammability (solid, gas): Decomposition temperature Auto igniting: Danger of explosion : Lower Explosion Limit: Upper Explosion Limit: Upper Explosion Limit: Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octor Solubility: Viscosity: Water: Stability and reactivity Reactivity: Conditions to avoid: Chemical stability:	Tightly sealed goggles Poperties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. hal/water: Not determined. Not det	
Physical and chemical provements of the second structure of the second structu	Tightly sealed goggles Poperties Aerosol. Aromatic Not determined. Undetermined. -44 °C (-47.2 °F) -19 °C (-2.2 °F) Extremely flammable. Not determined. Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol % Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. hal/water: Not determined. Not det	

(Contd. on page 4)

Printing date 01/17/2024

Revised On 01/17/2024

Page 4/5

(Contd	of	naga	21

	(Contd. of page 3	
11 Toxicological information		
LD/LC50 values that are relevant	for classification:	
13463-67-7 titanium dioxide		
Oral LD50 >20,000 mg/k	g (rat)	
Dermal LD50 >10,000 mg/k		
Inhalative LC50/4 h >6.82 mg/l (ra		
67-63-0 Isopropyl Alcohol	.,	
Oral LD50 4,570 mg/kg (rat)	
Dermal LD50 13,400 mg/kg		
Inhalative LC50/4 h 30 mg/l (rat)		
Information on toxicological effe	cts: No data available.	
Skin effects:	No irritant effect.	
Eye effects:	Irritating effect.	
Sensitization:	No sensitizing effects known.	
12 Ecological information	Llamandaria fan watan, da wat anantizinta duaina	
Aquatic toxicity: Persistence and degradability:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes.	
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons	
	(HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated	
	solvents.	
Bioaccumulative potential: Mobility in soil:	No further relevant information available. No further relevant information available.	
Other adverse effects:	No further relevant information available.	
13 Disposal considerations		
Dispose of in accordance with loca	l, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be	
disposed of responsibly. Do not hea	at or cut empty containers with electric or gas torches.	
Recommendation:	Completely empty cans should be recycled.	
Recommended cleansing agent:	Water, if necessary with cleansing agents.	
14 Transport information		
UN-Number	UN1950	
DOT	ŪN1950	
DOT	Aerosols, flammable	
ADR	1950 Aerosols	
Transport hazard class(es): Class	2.1 Gases	
Marine pollutant:	No	
Special precautions for user:	Warning: Gases	
EMS Number:	F-D,S-Ŭ	
Packaging Group:		
UN "Model Regulation":	UN1950, Aerosols, 2.1	
15 Regulatory information		
SARA Section 355 (extremely haz	zardous substances).	
None of the ingredients in this prod		
SARA Section 313 (Specific toxic		
108-88-3 Toluene		
67-63-0 Isopropyl Alcohol		
Toxic Substances Control Act		
(TSCA):	All hazardous ingredients are found on the inventory list of substances.	
Canadian Domestic Substances		
(DSL): Consumer Product Safety	All ingredients are listed or exempted.	
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
California Proposition 65 chemic		
13463-67-7 titanium dioxide		
100-41-4 ethyl benzene		
Prop 65 chemicals known to cause birth defects or reproductive harm:		
108-88-3 Toluene		
	(Contd. on page 5	

Page 5/5

Revised On 01/17/2024

Trade name: GLOSS MEDIUM BLU	£	
		(Contd. of page 4)
EPA:		
67-64-1 Acetone		
16 Other information		
Contact:	Regulatory Affairs	