1 Identification of the substance and manufacturer			
Trade name: BRAAP 5WAY CORROSION INHIBITOR AND LUBE			
Product code: Recommended use: Uses advised against: Manufacturer/Supplier:	00BW 160341 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com	Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com	
Emergency telephone number:	1-800-255-3924	· · · · · · · · · · · · · · · · · · ·	
2 Hazard(s) identification			
Classification of the substance or n	nixture		
Flammable Aerosols 1	H222 Extremely flammable aeros	ol.	
Gases under Pressure - Liquefied gas			
Eve Irritation 2A	H319 Causes serious eye irritation		
Carcinogenicity 1B	H350 May cause cancer.		
Specific Target Organ Toxicity - Single	2	izziness	
Specific Target Organ Toxicity - Repe Additional information:	ated Exposure 2 H373 May cause damage to organ		
GHS Hazard pictograms	$\land \land \land \land$		
	GHS02 GHS04 GHS07 GHS08		
Signal word	Danger		
Hazard statements	Extremely flammable aerosol.	4	
	Contains gas under pressure; may explode if hea Causes serious eve irritation.	ted.	
	May cause cancer.		
	May cause drowsiness or dizziness.		
	May cause damage to organs through prolonged	or repeated exposure.	
Precautionary statements	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot sur	faces No smoking	
	Do not spray on an open flame or other ignition s	ource.	
	Pressurized container: Do not pierce or burn, eve	n after use.	
	Do not breathe dust/fume/gas/mist/vapors/spray.		
	Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.		
	Wear protective gloves/protective clothing/eye pro	otection/face protection.	
	IF INHALED: Remove person to fresh air and kee	ep comfortable for breathing.	
	easy to do. Continue rinsing.	al minutes. Remove contact lenses, if present and	
	Call a poison center/doctor if you feel unwell.		
	If eye irritation persists: Get medical advice/atten	tion.	
	Store in a well-ventilated place.		
	Store locked up. Protect from sunlight. Do not expose to temperate	ures exceeding 50°C/122°E	
	Dispose of contents/container in accordance with	local/regional/national/international regulations.	
	·		

Chemical c Chemical D	haracterization: Mixtures rescription: This product is a mixture of the substances listed below with nonhazardous addition	ons.
Dangerous	components:	
	Mineral Oil	25-50%
67-64-1	Acetone	25-50%
64742-47-8	Mineral Spirits	15-25%
74-98-6	propane	5-10%
106-97-8	n-butane	1-5%
111-76-2	Glycol Ether EB	1-5%
64741-88-4	Parafinnic Petroleum oil	0.2-1%

4 First-aid measures	
After inhalation: After skin contact: After eye contact: After swallowing:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
	(Contd. on page 2)

Revised On 01/25/2024

Trade name: BRAAP 5WAY CORROSION INHIBITOR AND LUBE		
Most important symptoms and effects: Indication of any immediate medica	(Contd. of page 1)	
attention needed:	No further relevant information available.	
5 Fire-fighting measures Extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.	
Special hazards:	Can form explosive gas-air mixtures.	
Protective equipment for firefighters:	A respiratory protective device may be necessary.	
	·····,,,,,	
6 Accidental release measures		
Personal precautions, protective equipment and emergency		
procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.	
Methods and material for containment and cleaning up:	Ensure adequate ventilation.	
7 Handling and storage		
Precautions for safe handling	Use only in well ventilated areas.	
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.	
8 Exposure controls/personal prot	tection	
	equire monitoring at the workplace:	
	3	
PEL (USA) Long-term value: 5 mg/m <sup>3</sup> REL (USA) Short-term value: 10 mg/r Long-term value: 5 mg/m <sup>3</sup> oil mist	n <sup>3</sup>	
TLV (USA) L 67-64-1 Acetone		
PEL (USA) Long-term value: 2400 mg		
REL (USA) Long-term value: 590 mg/		
TLV (USA) Short-term value: 500 ppn Long-term value: 250 ppn A4, BEI	n 1	
74-98-6 propane		
PEL (USA) Long-term value: 1800 mg REL (USA) Long-term value: 1800 mg		
TLV (USA) see Appendix F Minimal o		
106-97-8 n-butane		
REL (USA) Long-term value: 1900 mg TLV (USA) Short-term value: 1000 pp (EX)		
111-76-2 Glycol Ether EB		
PEL (USA) Long-term value: 240 mg/ Skin		
REL (USA) Long-term value: 24 mg/n Skin	n³, 5 ppm	
TLV (USA) Long-term value: 20 ppm BEI, A3		
Ingredients with biological limit value	ues:	
67-64-1 Acetone BEI (USA) 25 mg/L		
Medium: urine Time: end of shift Parameter: Acetone (nons)		
111-76-2 Glycol Ether EB		
BEI (USA) 200 mg/g creatinine Medium: urine Time: end of shift		
Parameter: Butoxyacetic a		
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. (Contd. on page 3)	

	(Contd. of page 2) Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

## 9 Physical and chemical properties

Trade name: BRAAP 5WAY CORROSION INHIBITOR AND LUBE

o Filysical and chemical properties	
Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	0.5 Vol %
Upper Explosion Limit:	6.5 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water	: Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.

# 10 Stability and reactivity

Reactivity:	Stable at normal temperatures.	
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit.	Do not warehouse in subfreezing
	temperatures.	
Chemical stability:	Not fully evaluated.	
Possibility of hazardous reactions:	No dangerous reactions known.	
Incompatible materials:	No further relevant information available.	
Hazardous decomposition:	No dangerous decomposition products known.	

# **11 Toxicological information**

LD/LC50 values that are relevant for classification:			
111-76-2 Glycol Ether EB			
Oral	LD50	1,200 mg/kg (ATE)	
		1,480 mg/kg (rat)	
Dermal	LD50	400 mg/kg (rab)	
Inhalative	LC50/4 h	3 mg/l (ATE)	
		cological effects: No data available.	
Skin effec		No irritant effect.	
Eye effect	ts:	Irritating effect.	
Sensitizat	tion:	No sensitizing effects k	nown.
12 Ecologic	al inform	ation	
Aquatic to	oxicity:		o not empty into drains.
		gradability: The product is degrada	ble after prolonged exposure to natural weathering processes.
Other info	ormation:	This product does no (HCFC's), perfluoroca solvents.	ot contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons rbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated
Bioaccum	nulative po	tential: No further relevant info	rmation available.
Mobility in	n soil:	No further relevant info	rmation available.
-			(Contd. on page 4)

Revised On 01/25/2024

Page 4/4

Trade name: BRAAP 5WAY CORROSION INHIBITOR AND LUBE	

Other	adverse	effects:
-------	---------	----------

No further relevant information available.

(Contd. of page 3)

#### **13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. **Recommendation:** Completely empty cans should be recycled.

#### **14 Transport information**

UN-Number DOT	UN1950 UN1950
561	UN1950
DOT	DOT Aerosols, flammable
ADR	1950 Aerosols
Transport hazard class(es):	
Class	2.1 Gases
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-Ŭ
Packaging Group:	
UN "Model Regulation":	UN1950, Aerosols, 2.1

### **15 Regulatory information**

SARA Section 355 (extremely hazardous substances):		
None of the ingredients in this product are listed.		
SARA Section 313 (Specific toxic chemical listings):		
111-76-2 Glycol Ether EB		
Toxic Substances Control Act		
(TSCA): All hazardous ingredients are found on the inventory list of substances.		
Canadian Domestic Substances List		
(DSL): All ingredients are listed or exempted.		
Consumer Product Safety		
Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
California Proposition 65 chemicals known to cause cancer:		
None of the ingredients in this product are listed.		
Prop 65 chemicals known to cause birth defects or reproductive harm:		
None of the ingredients is listed.		
EPA:		
67-64-1 Acetone		
111-76-2 Glycol Ether EB NL		
6 Other information		

Contact:

Regulatory Affairs